



T SERIES (G3)

3-PHASE INVERTERS

The T Series inverter range is aimed at 3-phase domestic and small-scale commercial installations, offering unrivalled performance and versatility for increased yield potential and longer generation windows. The 3-phase T Series inverter options range from 3kW to 25kW.

REFINED – POWERFUL – FLEXIBLE



High Performance

Low start-up voltage, wide voltage range, 98.6% maximum efficiency



Upgradeable*

Fully optimised for upgrade to the FOX range of battery storage system

*Requires additional FOX equipment



IP65 Rated

Engineered to last with maximum suitability for outdoor installation



Remote Monitoring

Monitor your system remotely via smartphone app or web portal

ANYTIME, ANYWHERE REMOTE MONITORING PLATFORM

Monitor system performance in real-time via smartphone app or web portal using our advanced monitoring platform.



THE T SERIES (G3)



TECHNICAL SPECIFICATIONS

MODEL	T3-G3	T4-G3	T5-G3	T6-G3	T8-G3	T10-G3	T12-G3	T15-G3	T17-G3	T20-G3	T23-G3	T25-G3
INPUT (PV)												
Max. Input Power[W]	4500	6000	7500	9000	12000	15000	18000	22500	25500	30000	34500	37500
Max. Input Voltage[V]	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100
Start-up Input Voltage[V]	140	140	140	140	140	140	140	140	140	140	140	140
Rated Input Voltage[V]	600	600	600	600	600	600	600	600	600	600	600	600
MPPT Operating Voltage Range[V]	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000	140-1000
Max. Input Current[A]	14	14	14	14	14	14	14	28	28	28	28	28
Max. Short-circuit Current[A]	18.2	18.2	18.2	18.2	18.2	18.2	18.2	36.4	36.4	36.4	36.4	36.4
No. of Independent MPP Trackers	2	2	2	2	2	2	2	2	2	2	2	2
No. of Strings per MPP Tracker	1+1	1+1	1+1	1+1	1+1	1+1	1+1	2+2	2+2	2+2	2+2	2+2
OUTPUT (AC)												
Rated Output Power[W]	3000	4000	5000	6000	8000	10000	12000	15000	17000	20000	23000	25000
Max. Output Apparent Power[VA]	3300	4400	5500	6600	8800	11000	13200	16500	18700	22000	25300	27500
Rated Grid Voltage[V]	3/N/PE, 220/380, 230/400, 240/415											
Rated Grid Frequency[Hz]	50/60											
Rated Output Current[A]	4.3	5.8	7.2	8.7	11.6	14.5	17.4	21.7	24.6	29.0	33.3	36.2
Max. Output Current[A]	4.8	6.4	8.0	9.6	12.8	15.9	19.1	23.9	27.1	31.9	36.7	39.9
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)											
Total Harmonic Distortion [THDi]	<3%											
EFFICIENCY												
MPPT Efficiency							99.8%					
Euro Efficiency							97.8%					
Max. Efficiency							98.6%					
PROTECTION												
Insulation Monitoring							YES					
Residual Current Monitoring							YES					
PV String Current Monitoring	Yes						Optional					
DC Reverse Polarity Protection							YES					
Anti-islanding Protection							YES					
AC Short-circuit Protection							YES					
AC Overcurrent Protection							YES					
AC Overvoltage Protection							YES					
Surge Protection							DC/AC: Type II					
DC Switch							YES					
AFCI							YES					
GENERAL DATA												
Demensions (WxHxD)[mm]							370*480*183.5					
Weight	17	17	17	17	17	17	17	20	20	20	21	21
Cooling Method	Natural Convection						Fan					
Topology							Transformerless					
Noise Emission (typical)	<30	<30	<30	<30	<30	<30	<30	<55	<55	<55	<55	<55
Max. Operating Altitude							3000					
Operating Temperature Range							-25 ~ 60					
Humidity							0 ~ 100% (No Condensation)					
Protection Degree							IP65					
Internal Consumption at Night							<3					
Monitoring Module							WIFI / 4G (Optional)					
Communication							RS485, Meter, DRM, Estop					
Display							LCD, Touch Key, App, Website					
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)												
Safety	EN 62109-1/2, BIS IS 16169, BIS IS 16221-1/2											
EMC	EN 61000-6-1/2/3/4											
Grid Regulation	AS/NZS-4777.2, C10/11, EN50549-1, PN EN-50549-1, VDE-AR- N4105, RD 1699, CEI 0-21, NB/T 32004, VDE V 0126-1-1, UTE C 15-712-1											